

LED Wraparound

5-WATT, 6-CCT, Damp Rated, 130 lm/W, Dimmable

FEATURES

Lumen Output	1950 to 5460 lumens
Wattage	5-WATT (42W Max)
Efficacy	130 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
Size	4-FT
CCT	6-CCT (30K/35K/40K/50K/57K/65K)
Rating	Damp Location
Warranty	5 Years

APPLICATIONS

Premium indoor luminaire suitable for general indoors, lobbies, offices, meeting rooms, restrooms, hallways, stairwells, storage-closets, kitchens, and work-stations.

CONSTRUCTION

Manufactured for durability using aluminum sheet housing with semi-gloss coating to resist corrosion, discoloration, and scratching. Damp Location rated.

ELECTRICAL

Input voltages 120-277V models with 0-10V Continuous Dimming. Tunable 6-CCT (3000K, 3500K, 4000K, 5000K, 5700K, 6500K) and Tunable 5-Wattages. Operating temperatures -4°F to 104°F (-20°C to 40°C).

MOUNTING

Surface Mounting on ceilings or beams.

OPTICS

Anti-UV Frosted Polycarbonate Lens standard.

LISTINGS

DLC Premium listed. ETL certified to meet US and Canadian standards. FCC and RoHS compliant.

WARRANTY

5 year exclusive limited warranty.

Project:
Date:
Catalog No:
Prepared By:

4-FT 5-WATT 6-CCT Model



TUNABLE CORRELATED COLOR TEMPERATURES (CCT)



SPECIFICATIONS

ENERGY DATA

Input Voltage: 120-277V
Input Frequency: 50/60 Hz
Wattage: 5-WATT (42W Max)
Power Factor: >0.9
Total Harmonic Distortion (THD): <10%
Operating Temperature: -4°F to 104°F (-20°C to 40°C)

LIGHTING DATA

Lumens: 1950 to 5460
Lumens Per Watt: 130 lm/W
Correlated Color Temperature (CCT): 6-CCT (30K/35K/40K/50K/57K/65K)
Dimmable: 0-10V
Color Rendering Index (CRI): >80
L70: 50000 hours

ORDERING INFORMATION

Model	Size	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
WRP-4FT42W-XXK-G1	4-FT	(15W,	120-277V	0.14A@120V, 0.06A@277V	1950	130 lm/W	(3000K,	0-10V	White	48.00"L x 5.10"W x 1.90"H
		20W,		0.18A@120V, 0.08A@277V	2600		3500K,			
		30W,		0.28A@120V, 0.12A@277V	3900		4000K,			
		35W,		0.32A@120V, 0.14A@277V	4550		5000K,			
		42W)		0.39A@120V, 0.17A@277V	5460		5700K, 6500K)			

PHYSICAL DIMENSIONS

4-FT Model

48.00"L x 5.10"W x 1.90"H

